

## QUICK QBT 1000 - 1500 SERIES IP54 - IP65

Air Conditioning Electrical Panel

Elektrik Pano Kliması



| SPECIFICATIONS               | QBT 1000                      | OD - QBT 1000                 | QBT 1500                      | OD - QBT 1500                 | QBT 1700                      | OD - QBT 1700                 |
|------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Cooling Capacity (W)         | 1100 W                        | 1100 W                        | 1580 W                        | 1580 W                        | 1720 W                        | 1720 W                        |
| Rated Voltage/Frequency      | 220-230 Volt<br>50-60 Hz      | 220-230 Volt<br>50-60 Hz      | 220-230 Volt<br>50-60 Hz      | 220-230 Volt<br>50-60 Hz      | 220-230 Volt<br>50-60 Hz      | 220-230 Volt<br>50-60 Hz      |
| Starting Current (A)         | 12,1 A                        | 12,1 A                        | 14,8 A                        | 14,8 A                        | 14,8 A                        | 14,8 A                        |
| Running Current (A)          | 4,2 A                         | 4,3 A                         | 4,2 A                         | 4,3 A                         | 4,3 A                         | 4,5 A                         |
| Fuse (A)                     | 16 A                          | 16 A                          | 16 A                          | 16 A                          | 16 A                          | 16 A                          |
| Max. Pressure (BAR)          | 21-26 BAR                     | 21-26 BAR                     | 21-26 BAR                     | 21-26 BAR                     | 21-26 BAR                     | 21-26 BAR                     |
| Dimensions (h/w/d) mm        | 905x406x220 mm                | 905x406x276 mm                | 905x406x220 mm                | 905x406x276 mm                | 905x406x220 mm                | 905x406x276 mm                |
| Packed Dimensions (h/w/d) mm | 955x455x270 mm                | 955x455x320 mm                | 955x455x270 mm                | 955x455x320 mm                | 955x455x270 mm                | 955x455x320 mm                |
| Total Weight (kg)            | 36,0 Kg                       | 37,5 Kg                       | 37,0 Kg                       | 38,5 Kg                       | 37,0 Kg                       | 38,5 Kg                       |
| Gross Weight (kg)            | 37,5 Kg                       | 39,0 Kg                       | 38,5 Kg                       | 40,0 Kg                       | 38,5 Kg                       | 40,0 Kg                       |
| Internal Circuit             | 540 m <sup>3</sup> /h         | 540 m <sup>3</sup> /h         | 540 m <sup>3</sup> /h         | 540 m <sup>3</sup> /h         | 540 m <sup>3</sup> /h         | 540 m <sup>3</sup> /h         |
| External Circuit             | 945 m <sup>3</sup> /h         | 945 m <sup>3</sup> /h         | 945 m <sup>3</sup> /h         | 945 m <sup>3</sup> /h         | 945 m <sup>3</sup> /h         | 945 m <sup>3</sup> /h         |
| Power Absorbed (W)           | 680 W                         | 690 W                         | 710 W                         | 720 W                         | 710 W                         | 720 W                         |
| Type of Refrigerant          | R 134 a                       | R 134 a                       | R 134 a                       | R 134 a                       | R 134 a                       | R 134 a                       |
| Working Conditions (°C)      | + 20°C / +50°C                | + 20°C / +50°C                | + 20°C / +50°C                | + 20°C / +50°C                | + 20°C / +50°C                | + 20°C / +50°C                |
| Protection Degree            | IP 54                         | NEMA 4X                       | IP 54                         | NEMA 4X                       | IP 54                         | NEMA 4X                       |
| Mounting                     | Wall Mounted                  | Wall Mounted                  | Wall Mounted                  | Wall Mounted                  | Wall Mounted                  | Wall Mounted                  |
| Thermostat Setting (°C)      | 30 °C                         | 30 °C                         | 30 °C                         | 30 °C                         | 30 °C                         | 30 °C                         |
| Colour                       | ral 7035 - inox<br>black      | ral 7035 - inox<br>black      | ral 7035 - inox<br>black      | ral 7035 - inox<br>black      | ral 7035 - inox<br>black      | ral 7035 - inox<br>black      |
| Compressor                   | Secop / embraco               | Secop / embraco               | Secop / embraco               | Secop / embraco               | Secop / embraco               | Secop / embraco               |
| Fans                         | EbmPapst<br>High Quality Fans | EbmPapst<br>High Quality Fans | EbmPapst<br>High Quality Fans | EbmPapst<br>High Quality Fans | EbmPapst<br>High Quality Fans | EbmPapst<br>High Quality Fans |